

Chicago Metallic[®] Spanfast[®] Drywall Grid

Drywall ceiling suspension system



Ideal for: Condos, hotels, motels, suites, dorms, apartments, rest rooms, town homes, multi-housing and closets.

Performance Properties:

- Heavy duty drywall grid construction increases strength and decreases roll-over during installation.
- Pre-notched wall track allows for quick drywall grid installation
- This drywall grid ceiling system either reduces or eliminates the need for hanger wires at spans less than 7ft
- Sustainable: Minimum 25% recycled content, 100% locally recyclable
- Chicago Metallic[®] suspension systems meet a Class-A flame spread rating in accordance with ASTM standard E1264-08

Chicago Metallic® Spanfast® Drywall Grid



LEED® V4 HIGHLIGHTS

Materials and Resources (MR)

- Waste Management ✓ Planning ✓
- Interiors Life Cycle Impact Reduction ✓
- Environmental Product Declarations ✓
- Sourcing of Raw Materials ✓
- Material Ingredients ✓
- Waste Management ✓

Indoor Environmental Quality (EQ)


- ✓ -Low-Emitting Materials ✓
 - ✓ -Interior Lighting ✓
 - ✓ -Acoustic Performance ✓
- RECYCLED CONTENT: UP TO: 25%

Detail	Product Number	Length	Height (A)	Face (B)	Slotting / Class	Seismic	Recycled Content
Main Runners							
	640.SF.72	72"	1-1/2"	1-3/8"	hanger holes 5" OC, HD	C, DEF	25
	640.SF.96	96"	1-1/2"	1-3/8"	hanger holes 5" OC, HD	C, DEF	25
	640.SF.120	120"	1-1/2"	1-3/8"	hanger holes 5" OC, HD	C, DEF	25
	640.SF.144	144"	1-1/2"	1-3/8"	hanger holes 5" OC, HD	C, DEF	25
	640.SF.168	168"	1-1/2"	1-3/8"	hanger holes 5" OC, HD	C, DEF	25
Wall Angles & Channels							
	1450.00SF	144"	1-9/16"	1"	-	C, DEF	25


Packaging

Product Number	Pieces per Carton	Ft per Carton	Lbs per Carton	Cartons per Pallet	Lbs per Pallet
Main Runners					
640.SF.72	12	72	16	42	672
640.SF.96	12	96	22	42	924
640.SF.120	12	120	27	42	1134
640.SF.144	12	144	32	42	1344
640.SF.168	12	168	38	42	1596
Wall Angles & Channels					
1450.00SF	10	120	24	42	1008


Accessories




8501.01
9" x 9" GRG Access
Door and Frame
1 PC/Carton




8502.01
12" x 12" GRG
Access Door
and Frame
1 PC/Carton




8503.01
18" x 18" GRG
Access Door
and Frame
1 PC/Carton



8504.01
24" x 24" GRG
Access Door
and Frame
1 PC/Carton



8505.01
30" x 30" GRG
Access Door
and Frame
1 PC/Carton



VPCLIP.100
Variable Placement
Clip for Spanfast®
100 PCS/Carton



826.00H
2' Spacer Bar
80 LF/Carton



828.00H
4' Spacer Bar
160 LF/Carton



824.00H
4' Spacer Bar,
Notched at 2'
160 LF/Carton

Performance


Component Load Test Data and Material

Allowable Load per ASTM C645											
			Allowable Load (lb/ft ²) With No Lateral Bracing								
Furring Runner	Length	Spacing	4'	5'	6'	7'	8'	10'	12'	14'	14' Two Supports at 1/3
640.SF.72	72"	16"	-	-	6.05	-	-	-	-	-	-
	72"	24"	-	-	4.03	-	-	-	-	-	-
640.SF.96	96"	16"	18.8	-	-	-	18.8 MSS	-	-	-	-
	96"	24"	12.5	-	-	-	12.5 MSS	-	-	-	-
640.SF.120	120"	16"	-	10.23	-	-	-	10.23 MSS	-	-	-
	120"	24"	-	6.8	-	-	-	6.8 MSS	-	-	-
640.SF.144	144"	16"	-	-	6.05	-	-	-	6.05 MSS	-	-
	144"	24"	-	-	4.03	-	-	-	4.03 MSS	-	-
640.SF.168	168"	16"	-	-	-	3.86, 28.57 MSS	-	-	-	3.86 MSS	12.23 2xMSS
	168"	16"	-	-	-	19.0 MSS	-	-	-	-	8.14 2xMSS

Hanger wires are eliminated in many applications, and are reduced vs. standard drywall grid at spans greater than 7', minimizing labor and material costs.

*MMS - with Mid-Span Support

Component Load Test Data



Material

ASTM C 635 Heavy Duty (HD) furring runner classification; commercial quality 0.20 steel, G40 hot-dip galvanized body and knurled face cap, 1-3/8" width, 1-1/2" height.

Note: A metallurgist should be consulted regarding the suitability of this product for the environmental conditions in which it is being installed.

Rockfon® is a registered trademark
of the ROCKWOOL Group.

04.2019 | All colour codes mentioned are based on the NCS - Natural Colour System® property of and used on license from NCS Colour AB, Stockholm 2012 or the RAL colour standard. Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

Rockfon
4849 S. Austin Ave., Chicago, IL 60638 USA
Tel. +1-800-323-7164
Fax. +1-800-222-3744
www.rockfon.com
cs@rockfon.com
360003046

