

DATASHEET

# Chicago Metallic™ Monolithic




**Sounds Beautiful**


# Chicago Metallic™ Monolithic

- T and Omega shaped grid for the installation of Rockfon® Mono Acoustic and a variety of boards
- Quick and easy click system reduces time and installation costs
- Single layer system for reduced plenum heights
- Simple grid without the need for accessories

## Cross-section




## Compatible tiles











## Coupling

Joggled end






## Assortment

Product group		Component description	Height (mm)	Length (mm)	Colour	Pcs per pack	Lm per pack	Kg per pack	Carton per pallet	Kg per pallet
Main runner										
MONO T35 MR		Monolithic main runner	38	3600	69	20	72	37,1	32	1187
MONO T35 MR			38	3600	69	20	72	37,1	32	1187
Cross tee										
MONO HAT35 CT		Monolithic furring channel	22,23	1200	69	50	60	25	48	1200
Wall angle options										
MONO C40		Galvanised C-wall angle 30x40.5x30 mm	40,5	3050	69	10	30,5	10,74	60	666.4
Accessories										
NH 90		Upper part nonius hanger	85			100		2,4		
NH CLIP		Intersection clip for nonius				200		1,3		
NH T		Lower part nonius hanger for T profiles				100		3,9		
HDC W2		Steel perimeter hold down clip – height 40 mm - combinable with C37 wall angle				500		4,03		
SH 50		Suspension clip (curved) for Chicago Metallic™ T-profiles + securing nail	50			100		2,5		

Contact Rockfon® for the full range of wall angles and accessories.



## Position of slots and suspension holes

Product group	Component description	Height (mm)	Length (mm)	Slots	Distance between slots (mm)
MONO T35 MR	Monolithic main runner	38	3600	18	
MONO T35 MR		38	3600	16	
MONO HAT35 CT	Monolithic furring channel	22,23	1200	0	

## Performance



### Load bearing capacity

Kg/m <sup>2</sup>		
Hanger distance (mm)	Module size (mm)	Maximum deflection
1200	1200 x 600	3.3 mm
1200	1200 x 400	12
		13.9



### Reaction to fire

A1



### Corrosion resistance

B



### Environment

Fully Recyclable

# Understanding the performance of Chicago Metallic™ grids and accessories



## Reaction to fire

Reaction to fire is classified in accordance with EN 13501-1. Chicago Metallic steel grids and accessories are non-combustible.



## Fire resistance

A range of Chicago Metallic steel grids are tested in combination with different Rockfon tiles and are classified in accordance with European norm EN 13501-2 and/or national norms.



## Colours

Chicago Metallic grids are available in various colours from the RAL and NCS systems, which are measured following the ISO 7724-2 and ISO 7724-3 standards. The actual colours may deviate slightly from the RAL and NCS references.

Chicago Metallic grids are available in a variety of finishes from matt to high gloss, with a respective average of < 5, 15 and 50 units at a 60° angle. The matt finishing is measured at an angle of 85°. See the colour legend for their average values. The gloss unit is measured in accordance with EN13523 part 2.



## Corrosion resistance

Chicago Metallic products produced from hot dip galvanised steel following the Sendzimir process comply with the corrosion classes of the product standard EN 13964 (A, B, C, D). The standard systems in class B are protected with 100 g/m<sup>2</sup> zinc evenly applied on both sides. The enhanced corrosion resistance (ECR) systems and accessories in class C or D have respectively a layer of 100 g/m<sup>2</sup> and 275 g/m<sup>2</sup> zinc evenly applied on both sides and are protected with an additional layer of 20 micron paint per side.



## Load bearing performance

The load bearing performance (max. kg/m<sup>2</sup> load applicable to the grid system without exceeding the allowable deflection of the individual components) is tested in accordance with the EN 13964 standard. The accumulative value of the system deflection, shown on the data sheets, does not exceed the max. deflection as given in class 1 of the standard. Special project configurations deviating from the standard module sizes mentioned in the data sheets must be calculated by Rockfon technical services.



## Cleaning

All Chicago Metallic grids can be cleaned with water and a mild detergent in combination with a melamine foam sponge or microfiber cloth.

## Colour legend

For colour availability of individual components, please check the assortment table above

White 001 RAL 9003	White 901 RAL 9010	White 01 White 916	Matt White 11 RAL 9003	L value: 93 Gloss: 2 at both a 60° and 85° angle
Platinum 54 RAL 7035	Alugrey 04 RAL 9006	Galvanised 00 Galvanised 69	Matt Black 88 RAL 9004	Gloss: 4.5 at 60° angle and 11.5 at 85° angle
Brushed Alu 534	High Gloss Chrome 14	Carrara 57	High Gloss Brass 16	
White 001 / White 001 (8WW) RAL 9003 / RAL 9003	Black 08 / Black 08 (8BB) RAL 9005 / RAL 9005	White 001 / Black 08 (8WB) RAL 9003 / RAL 9005	Alugrey 04 / Black 08 (8GB) RAL 9006 / RAL 9005	

# Rockfon Color-all®

<p>Mustard - 51</p> <p>NCS S 2050-Y10R</p>	<p>Sand - 30</p> <p>NCS S 2020-Y20R</p>	<p>Stucco - 20</p> <p>NCS S 1505-Y30R</p>			
<p>Scarlet - 71</p> <p>NCS S 6030-Y80R</p>	<p>Coral - 76</p> <p>NCS S 3040-Y90R</p>	<p>Seashell - 75</p> <p>NCS S 1510-Y60R</p>	<p>Petal - 74</p> <p>NCS S 1005-Y60R</p>		
<p>Seaweed - 34</p> <p>NCS S 8005-G20Y</p>	<p>Eucalyptus - 32</p> <p>NCS S 6020-B90G</p>	<p>Sage - 31</p> <p>NCS S 3010-G10Y</p>	<p>Mint - 12</p> <p>NCS S 1005-G10Y</p>		
<p>Space - 49</p> <p>NCS S 7020-B</p>	<p>Storm - 48</p> <p>NCS S 6020-R90B</p>	<p>Azure - 47</p> <p>NCS S 3020-B</p>	<p>Fresh - 42</p> <p>NCS S 2010-B10G</p>		
<p>Earth - 25</p> <p>NCS S 5010-Y50R</p>	<p>Clay - 26</p> <p>NCS S 5005-G80Y</p>	<p>Linen - 22</p> <p>NCS S 4005-Y50R</p>	<p>Sandalwood - 13</p> <p>NCS S 2010-Y60R</p>	<p>Chalk - 21</p> <p>NCS S 2005-Y40R</p>	
<p>Ebony - 28</p> <p>NCS S 8505-Y80R</p>	<p>Cork - 24</p> <p>NCS S 4010-Y30R</p>	<p>Hemp - 23</p> <p>NCS S 3005-Y20R</p>			
<p>Iron - 18</p> <p>NCS S 7502-B</p>	<p>Concrete - 06</p> <p>NCS S 6000-N</p>	<p>Mastic - 17</p> <p>NCS S 4000-N</p>	<p>Zinc - 05</p> <p>NCS S 4005-R50B</p>	<p>Mercury - 62</p> <p>NCS S 2502-B</p>	
<p>Charcoal - 09</p> <p>NCS S 8500-N</p>	<p>Anthracite - 08</p> <p>NCS S 7010-R90B</p>	<p>Gravel - 03</p> <p>NCS S 3502-B</p>	<p>Plaster - 02</p> <p>NCS S 2005-R80B</p>	<p>Stone - 01</p> <p>NCS S 2000-N</p>	<p>Moon - 10</p> <p>NCS S 1005-R80B</p>

NCS codes are closest colour match. The actual colour of the Rockfon Color-all® grid may deviate slightly from printed colours due to the texture of the surface. Samples are available upon request.

# Sounds Beautiful

