

DATASHEET

Rockfon Blanka® dB 41



Sounds Beautiful

Rockfon Blanka® dB 41











- Combines enhanced room-to-room sound insulation as well as a high level of sound absorption (Class A) for a flexible and quiet office layout
- Made from a 35mm stone wool core with a high-performance membrane on the back which reduces the transmission of noise from room-to-room
- The enhanced surface durability makes it more resistant to dirt and everyday wear and tear, enhancing the product lifetime
- Wide range of dimensions in concealed, semi-concealed and visible grid options
- Light weight sound insulating tile, easy to install/cut and clean with a vacuum or damp cloth

Product Description

- Stone wool tile
- Visible side: smooth, deep-matt and super-white painted fleece
- Rear side: high-performance membrane
- Durable painted edges

Application Areas

- Office
- Healthcare
- Education

Edge detail	Module size (mm)	Weight (kg/m ²)	MS / MS easy access (mm)	Recommended installation system	Recycled content	Cradle to Cradle Certified®	A1-A3 Production stage impact (kg CO ₂ eq/m ²)*	A1-C4 Full life cycle impact (kg CO ₂ eq/m ²)*
 A24	600 x 600 x 35	5,6	50 / 150	Rockfon® System dB T24 A, E™	37%		4,73	6,31
	1200 x 600 x 35		50 / 150	Rockfon® System dB T24 A, E™				
			50 / 150	Rockfon® System dB Bandraster A™				
 D	600 x 600 x 35	5,6	62 / 87	Rockfon® System XL T24 D™	37%		4,73	6,31
	1200 x 600 x 35		69 / 69	Rockfon® System T24 Stepped Z D™				
 D/AEX	1200 x 600 x 35	5,6	150 / 150	Rockfon® System Bandraster Dzn/AEX™	37%		4,73	6,31
	1500 x 600 x 35		150 / 150	Rockfon® System Bandraster Dzn/AEX™				
	1800 x 600 x 35		150 / 150	Rockfon® System Bandraster Dzn/AEX™				
 E15	600 x 600 x 35	5,6	60 / 150	Rockfon® System T15 E™	37%		4,73	6,31
	1200 x 600 x 35		60 / 150	Rockfon® System T15 E™				
 E24	600 x 600 x 35	5,6	60 / 150	Rockfon® System dB T24 A, E™	37%		4,73	6,31
	1200 x 600 x 35		60 / 150	Rockfon® System dB T24 A, E™				

MS = Minimum suspension

MS easy access = Minimum suspension - tiles demountable

* For full environmental impact disclosure, see our product EPDs available on rockfon.link/cee-epd. Due to differences in calculation methods and scenario assumptions, environmental impact values are generally not directly comparable between manufacturers.

Performance



Sound absorption
 α_w : 0,90 (Class A)



Direct sound insulation
 R_w = 21 dB



Sound insulation improvement
 Plenum 1000 mm
 - ΔR_w = 9 dB
 - $\Delta(R_w+C)$; $\Delta(R_w+C_{tr})$ = 8 ; 6 dB

Plenum 620 mm
 - ΔR_w = 8 dB
 - $\Delta(R_w+C)$; $\Delta(R_w+C_{tr})$ = 7 ; 5 dB

Plenum 350 mm
 - ΔR_w = 9 dB
 - $\Delta(R_w+C)$; $\Delta(R_w+C_{tr})$ = 7 ; 4 dB

Plenum 160 mm
 - ΔR_w = 6 dB
 - $\Delta(R_w+C)$; $\Delta(R_w+C_{tr})$ = 5 ; 2 dB

Weighted sound reduction improvement
 performance measured in accordance with EN ISO 10140-series



Room to room sound insulation
 $D_{n,f,w}$ = 41 dB

$D_{n,f,w}$ with Rockfon Soundstop 21 dB = 50* dB
 $D_{n,f,w}$ with Rockfon Soundstop 30 dB = 55* dB
 The sound insulation properties (R_w , $D_{n,f,w}$) presented in the datasheet represent A-edge tiles.
 *) Values obtained on the basis of theoretical analysis.



Reaction to fire
 A2-s1,d0



Light reflection and light diffusion
 87% light reflection
 >99% light diffusion



Humidity and sag resistance
 Up to 100% RH.
 No visible deflection in high humidity
 C/0N



Cleaning
 - Vacuum
 - Damp cloth



Hygiene
 Stone wool provides no sustenance to microorganisms




Surface durability
 Enhanced durability and dirt resistance.

Wet-scrub resistance: Class 4

The wet-scrub resistance is tested in accordance with EN ISO 11998:2007 and rated following EN 12720:2009+A1:2013 scale going from 1 to 5, where 5 is the best.



Thermal insulation
 Thermal conductivity:
 λ_D = 40 mW/mK



Visual appearance

Super-white surface
 L value: 94.5

The whiteness (L value) of the product is tested in accordance with ISO 7724 and measured on a scale from 1 (black) to 100 (white).

Deep matt surface, perfect in critical side-light

Gloss: 0.8 gloss unit at 85° angle

The gloss of the product is tested in accordance with ISO 2813.



Recyclability

Fully recyclable stone wool



Indoor environment

Rockfon ceiling products are classified in Class E1 in accordance with EN 13964 (EN 717-1). Rockfon ceiling products have a very low release of VOCs. A selection of Rockfon products have achieved the following performance levels and labels in indoor air emissions:



Material Health

All materials used in Rockfon products are screened against the technical checklist A20 and the list of substances restricted under REACH and do not contain substances of very high concern (SVHC). Rockfon stone wool fibres comply with safe fibre EU regulation and hold a EUCEB certification.

Sounds Beautiful

