


DATASHEET

Rockfon Eclipse® Customised



Sounds Beautiful

Rockfon Eclipse® Customised


- Innovative and aesthetically pleasing frameless acoustic island comes in a smooth, matt surface with an unlimited custom colour range using NCS
- Rockfon Eclipse Customised is available in an unlimited variety of shapes, allowing for unique design freedom to inspire and enhance your interior design scheme
- Quick and easy to install, Rockfon Eclipse Customised can be used alone or where a traditional suspended ceiling cannot be installed
- Perfect for thermal mass installations with rear surface providing excellent heat and light reflection

Product Description

- Stone wool island
- Visible side: smooth custom-coloured, matt fleece
- Rear side: white backing fleece
- Painted edges

Application Areas

- Retail
- Education
- Office
- Leisure

| Edge detail | Shapes | Module size (mm) | Weight (kg/unit) | MS / MS easy access (mm) | Recommended installation System | Recycled content | Cradle to Cradle Certified® | A1-A3 Production stage impact (kg CO ₂ eq/m ²)* | A1-C4 Full life cycle impact (kg CO ₂ eq/m ²)* |
|---|---|------------------|------------------|--------------------------|---------------------------------|------------------|---|--|---|
|  |  | 1160 x 1160 x 40 | 9 | 55 / 55 | Rockfon® System Eclipse Island™ | 35% |  | 6,31 | 8,21 |
| |  | 1160 x 580 x 40 | 5 | 190 / 190 | Rockfon® System Eclipse Island™ | | | | |
| | | 1760 x 1160 x 40 | 13 | 190 / 190 | Rockfon® System Eclipse Island™ | | | | |
| | | 2360 x 1160 x 40 | 17 | 190 / 190 | Rockfon® System Eclipse Island™ | | | | |
| |  | 800 x 800 x 40 | 3 | 190 / 190 | Rockfon® System Eclipse Island™ | | | | |
| |  | 1160 x 1160 x 40 | 7 | 190 / 190 | Rockfon® System Eclipse Island™ | | | | |
| | | | 4 | 190 / 190 | Rockfon® System Eclipse Island™ | | | | |
| | | | 6 | 190 / 190 | Rockfon® System Eclipse Island™ | | | | |
| |  | 1760 x 1160 x 40 | 10 | 190 / 190 | Rockfon® System Eclipse Island™ | | | | |
| |  | 1760 x 1160 x 40 | 10 | 190 / 190 | Rockfon® System Eclipse Island™ | | | | |
| |  | - x - x 40 | - | - | Rockfon® System Eclipse Island™ | | | | |

MS = Minimum suspension

MS easy access = Minimum suspension - tiles demountable

Contact us for special shapes, sizes, two-sided painted Eclipse Customised, lead times and minimum order quantities.

Free-form sizes bigger than 2400 length or 1200 width will be produced as two halves.

Size 2360 x 1160 x 40 is only available in custom colours on one side.

Note: MS / MS easy access 190 mm is very comfortable for the installer. Within this height he has 150 mm space above the upper surface of the tile for handling. In practice this height can be considerably reduced, even down to 110 mm, resulting in reducing also the MS / MS easy access down to 150 mm.

* For full environmental impact disclosure, see our product EPDs available on rockfon.link/cee-epd. Due to differences in calculation methods and scenario assumptions, environmental impact values are generally not directly comparable between manufacturers.




Performance



Sound absorption

A_{eq} (m²/item)

* Distance between items greater or equal to 2000mm. Further acoustic data available; contact your local Rockfon technical support.



| | 125 Hz | 250 Hz | 500 Hz | 1000 Hz | 2000 Hz | 4000 Hz |
|--|--------|--------|--------|---------|---------|---------|
| Square 1160 single item* (suspension height: 15mm) | 0.3 | 0.9 | 1.8 | 2.0 | 1.8 | 1.6 |
| Square 1160 single item* (suspension height: 500mm) | 0.6 | 1.3 | 1.9 | 2.6 | 2.7 | 2.6 |
| Square 1160 array of 6 items, 300mm distance (suspension height 500mm) | 0.5 | 1.1 | 1.8 | 2.2 | 2.4 | 2.3 |



Reaction to fire

A2-s1,d0



Light reflection

Colour-dependent



Humidity and sag resistance

Up to 100% RH.
No visible deflection in high humidity



Cleaning

- Vacuum



Hygiene

Stone wool provides no sustenance to microorganisms



Recyclability

Fully recyclable stone wool



Indoor environment

Rockfon ceiling products are classified in Class E1 in accordance with EN 13964 (EN 717-1).



Material Health

All materials used in Rockfon products are screened against the technical checklist A20 and the list of substances restricted under REACH and do not contain substances of very high concern (SVHC). Rockfon stone wool fibres comply with safe fibre EU regulation and hold a EUCB certification.

The properties presented on this datasheet cover the majority of the NCS colour selection. For detailed information on specific NCS colours please contact Rockfon Customer Service.

Rockfon production facilities are certified according to the ISO 9001 and ISO 14001 management systems standards.

Sounds Beautiful

