



Chicago Metallic[™] Ultraline[®] 3500

Datasheet



Chicago Metallic™ Ultraline® 3500

- Creates a narrow recess in the grid for an aesthetic, 'designer' ceiling
- The narrow recess and crisply mitred intersections result in flawless continuous lines and an aesthetically pleasing smooth and level appearance
- Available in Standard White 001 or black 08 on both sides of the grid
- Also available in combinations of grey/black or white/black for a colour contrast
- Functional recess allows for the easy integration of partitions, track lighting and signage


Cross-section



Compatible tiles



Coupling






Assortment

Product group		Component description	Height (mm)	Length (mm)	Colour	Pcs per pack	Lm per pack	Kg per pack	Carton per pallet	Kg per pallet
Main runner										
UL MR		Ultraline® main runner	41	3600	8GB, 8BB, 8WB	20	72	28.9	50	1446
UL MR			41	3600	8WW	20	72	28.9	50	1446
Cross tee										
UL CT		Ultraline® cross tee	41	600	8WW	70	42	16.4	72	1184
UL CT			41	600	8GB, 8BB, 8WB	70	42	16.4	72	1184
UL CT		Ultraline® cross tee - with 1 slot	41	1200	8GB, 8BB, 8WB	40	48	18.7	70	1312
UL CT			41	1200	8WW	40	48	18.7	70	1312

Contact Rockfon® for the full range of wall angles and accessories.
For colour references, please see table below.



Position of slots and suspension holes

Product group	Component description	Height (mm)	Length (mm)	Slots	Distance between slots (mm)
UL MR	Ultraline® main runner	41	3600	6	 300 / 600 / 4 x 600 / 300
UL CT	Ultraline® cross tee	41	600	0	 600
UL CT	Ultraline® cross tee - with 1 slot	41	1200	1	 600 / 600

Special lengths and slot patterns are available upon request.

Performance



Load bearing capacity

Hanger distance (mm)	Module size (mm)	Kg/m ²	
		Maximum deflection	
		2.5 mm	4.0 mm
1200	600 x 600	9.8	16.3
1200	1200 x 600	10.7	17.6
1250	625 x 625	7.8	13.2
1250	1250 x 625	8.6	14.2
1200	675 x 675	6.5	10.9
1200	1350 x 675	7.2	12.0
1350	675 x 675	5.1	8.7
1350	1350 x 675	5.6	9.5



Reaction to fire

A1



Corrosion Resistance

C



Environment

Fully recyclable

Understanding the performance of Chicago Metallic™ grids and accessories



Reaction to fire

Reaction to fire is classified in accordance with EN 13501-1. Chicago Metallic steel grids and accessories are non-combustible.



Fire resistance

A range of Chicago Metallic steel grids are tested in combination with different Rockfon tiles and are classified in accordance with European norm EN 13501-2 and/or national norms.



Colours

Chicago Metallic grids are available in various colours from the RAL and NCS systems, which are measured following the ISO 7724-2 and ISO 7724-3 standards. The actual colours may deviate slightly from the RAL and NCS references. Chicago Metallic grids are available in a variety of finishes from matt to high gloss, with a respective average of < 5, 15 and 50 units at a 60° angle. The matt finishing is measured at an angle of 85°. See the colour legend for their average values. The gloss unit is measured in accordance with EN13523 part 2.



Corrosion resistance

Chicago Metallic products produced from hot dip galvanised steel following the Sendzimir process comply with the corrosion classes of the product standard EN 13964 (A, B, C, D). The standard systems in class B are protected with 100 g/m² zinc evenly applied on both sides. The enhanced corrosion resistance (ECR) systems and accessories in class C or D have respectively a layer of 100 g/m² and 275 g/m² zinc evenly applied on both sides and are protected with an additional layer of 20 micron paint per side.



Load bearing performance

The load bearing performance (max. kg/m² load applicable to the grid system without exceeding the allowable deflection of the individual components) is tested in accordance with the EN 13964 standard. The accumulative value of the system deflection, shown on the data sheets, does not exceed the max. deflection as given in class 1 of the standard. Special project configurations deviating from the standard module sizes mentioned in the data sheets must be calculated by Rockfon technical services.



Cleaning






















All Chicago Metallic grids can be cleaned with water and a mild detergent in combination with a melamine foam sponge or microfiber cloth.

Colour legend

For colour availability of individual components, please check the assortment table above

White 001 RAL 9003	White 901 RAL 9010	White 01 White 916	Matt White 11 RAL 9003	L value: 93 Gloss: 2 at both a 60° and 85° angle
Platinum 54 RAL 7035	Alugrey 04 RAL 9006	Galvanised 00 Galvanised 69	Matt Black 88 RAL 9004	Gloss: 4.5 at 60° angle and 11.5 at 85° angle
Brushed Alu 534	High Gloss Chrome 14	Carrara 57	High Gloss Brass 16	
White 001 / White 001 (8WW) RAL 9003 / RAL 9003	Black 08 / Black 08 (8BB) RAL 9005 / RAL 9005	White 001 / Black 08 (8WB) RAL 9003 / RAL 9005	Alugrey 04 / Black 08 (8GB) RAL 9006 / RAL 9005	

Rockfon Color-all®



NCS codes are closest colour match. The actual colour of the Rockfon Color-all® grid may deviate slightly from printed colours due to the texture of the surface. Samples are available upon request.

Rockfon® is a registered trademark
of the ROCKWOOL Group.

 [linkedin.com/company/Rockfon-as](https://www.linkedin.com/company/Rockfon-as)

 [pinterest.com/Rockfon](https://www.pinterest.com/Rockfon)

 [youtube.com/RockfonOfficial](https://www.youtube.com/RockfonOfficial)

 [facebook.com/RockfonOfficial](https://www.facebook.com/RockfonOfficial)

 [instagram.com/Rockfon_Official](https://www.instagram.com/Rockfon_Official)

Sounds Beautiful

03/2022 | All colour codes mentioned are based on the NCS - Natural Colour System® property of and used on license from NCS Colour AB, Stockholm 2012 or the RAL colour standard. Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.



Rockfon
ROCKWOOL Limited T/A Rockfon
14th Floor, Chiswick Tower, 389 Chiswick High Road,
London W4 4AL
Tel: +44 (0) 208 222 7457
www.rockfon.co.uk