

DATASHEET

# **Rockfon® Industrial Black**



# **Rockfon® Industrial Black**

- Black finish which can be used in their own right to create a ceiling or be placed behind other surfaces
- Low weight ( $4.0 kg/m^2$ ), quick and easy to install
- Highest sound absorption (Class A)

#### **Product Description**

- Stone wool tile

- Visible side: pre-finished surface

- Rear side: back fleece

#### **Application Areas**

- Industry
- Education

Edge detail	Module size (mm)	Weight (kg/m²)	MS / MS easy access (mm)	Recommended installation System	Recycled content	Cradle to Cradle Certified®	A1-A3 Production stage impact (kg CO <sub>2</sub> eq/m²)*	A1-C4 Full life cycle impact (kg CO₂ eq/m²)*
A24	1200 x 600 x 50	4.0	50 / 200	Rockfon® System T24 A™	39%	CERTIFIED © Cradle to cradle	3.38	4.49

MS = Minimum Suspension

<sup>\*</sup> For full environmental impact disclosure, see our product EPDs available on rockfon.link/uk-epd. Due to differences in calculation methods and scenario assumptions, environmental impact values are generally not directly comparable between manufacturers.



# **Performance**



Sound absorption  $\alpha_{w}$ : up to 1.00 (Class A)

Thickness (mm) /

	0							
	1.0							
(	).9							
	0.8							
· ·	0.0							
(	).7 +							
(	).6							
$\alpha_{p}$ (	).5 +							
,	).4							
(	).3 +/							
(	).2							
(	).1							
Th:-!/\/	).0 +							
THICKHESS (IIIII) /								
Suspension (incl. tile - mm)	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	$\alpha_{w}$	
, ,	123 112	230 112	300 112	1000 112	2000 112	4000 T12	C.W	
								Γ
50 / 200	0.55	0.90	1.00	1.00	1.00	1.00	1.00	ı
50 / 200	0.55	0.90	1.00	1.00	1.00	1.00	1.00	

Absorption class NRC 1.00 Α 1.00 Α 1.00



## Reaction to fire

Α1



#### Humidity and sag resistance

Up to 100% RH. No visible deflection in high humidity C/0N



#### Cleaning

- Vacuum



### Hygiene

Stone wool provides no sustenance to microorganisms



#### Thermal insulation

Thermal conductivity:  $\lambda_D = 37 \text{ mW/mK}$ 



0.70

50 / 50

0.20

#### Recyclability

1.00

Fully recyclable stone wool

1.00

1.00



#### Indoor environment

Rockfon ceiling products are classified in Class E1 in accordance with EN 13964 (EN 717-1). Rockfon ceiling products have a very low release of VOCs. A selection of Rockfon products have achieved the following performance levels and labels in indoor air emissions:

1.00







### Material Health

All materials used in Rockfon products are screened against the technical checklist A20 and the list of substances restricted under REACH and do not contain substances of very high concern (SVHC). Rockfon stone wool fibres comply with safe fibre EU regulation and hold a EUCEB certification.

# **Sounds Beautiful**