

Chicago Metallic™ L Profiles






Datasheet



Chicago Metallic™ L Profiles


- Visible sides adapted to the variety of grid widths
- Perfect colour match with ceiling grids
- Choice of different heights for installation purposes

Assortment

Product group		Component description	Length (mm)	Colour	Pcs per pack	Lm per pack	Kg per pack
Wall angle options							
L24x24		L Wall angle 24 x 24mm	3000	02	40	120	19.7
L24x24			3000	02	40	120	16.8
L19x24		L Wall angle 19 x 24mm	3000	02	42	126	19.64
L20x14		L Wall angle 20 x 14mm	3000	02	40	120	14.78
L24x14		L Wall angle 24 x 14mm	3000	02	40	120	15.6


Product description

L24x24




- • Symmetrical 24 x 24mm wall angle with hemmed edges
 - Profile can be used from both sides
 - Material thickness: 0.4mm
- Body Material thickness**0.4mm

L24x24



- • Symmetrical 24 x 24mm wall angle with hemmed edges
 - Profile can be used from both sides
 - Material thickness: 0.4mm
- Body Material thickness**0.33mm


L19x24



- • Asymmetrical 19 x 24mm wall angle with hemmed edges
 - Profile can be used from both sides
 - Material thickness: 0.4mm
- Body Material thickness**0.4mm


Product description

L20x14



- • Asymmetrical 20 x 14mm wall angle with hemmed edges
 - Profile can be used from both sides
 - Narrow face to meet high aesthetic requirements
 - Material thickness: 0.4mm
- Body Material thickness**0.4mm

L24x14



- • Asymmetrical 24 x 14mm wall angle with hemmed edges
 - Profile can be used from both sides
 - Narrow face to meet high aesthetic requirements
 - High mounting surface of 24mm
 - Material thickness: 0.4mm
- Body Material thickness**0.4mm

Performance



Reaction to fire

Non-combustible



Environment

Fully Recyclable

Rockfon® is a registered trademark
of the ROCKWOOL Group.

 [linkedin.com/company/Rockfon-as](https://www.linkedin.com/company/Rockfon-as)

 [pinterest.com/Rockfon](https://www.pinterest.com/Rockfon)

 [youtube.com/RockfonOfficial](https://www.youtube.com/RockfonOfficial)

 [facebook.com/RockfonOfficial](https://www.facebook.com/RockfonOfficial)

 [instagram.com/Rockfon_Official](https://www.instagram.com/Rockfon_Official)

03.2022 | All colour codes mentioned are based on the NCS - Natural Colour System® property of and used on
license from NCS Colour AB, Stockholm 2012 or the RAL colour standard. Subject to alterations in range and product
technology without prior notice. Rockfon accepts no responsibility for printing errors.

Sounds Beautiful

Rockfon Singapore

ROCKWOOL Building Materials
(Singapore) Pte Ltd.
No. 7, Tuas Avenue 1
Jurong Town,
Singapore 639492
Tel: (+65) 6861 4722
Fax: (+65) 6862 3533
E-mail: enquiry@rockfon.com
en.rockfon.international

Rockfon Hong Kong

ROCKWOOL Building Materials
(Hong Kong) Ltd.
Unit 301-2, 3/F, Koon Wah Building,
No.2 Yuen Shun Circuit,
Yuen Chau Kok, Shatin,
N.T., Hong Kong
Tel: (+852) 2576-6117
Mobile: (+852) 9161-7924
E-mail: enquiry@rockfon.com
en.rockfon.international

Rockfon

ROCKWOOL Middle East FZE
Office 139, Building 6WB, DAFZA
P. O. Box 293585, Dubai, UAE

Tel: +971-4-214-6280
E-mail: rockfonme@rockfon.com
en.rockfon.international

Rockfon

ROCKWOOL France S.A.S.
111, rue du Château des Rentiers
75013 Paris

Tel: +33 1 40 77 82 82
Fax.: +33 1 45 86 77 90
E-mail: info@rockfon.fr
www.rockfon.fr

