

Chicago Metallic™ W Profiles







Datasheet



Chicago Metallic™ W Profiles


- A range of W profiles (shadow moulding wall angles) for various applications
 - C profile for tiles up to 37mm
- Visible flanges from 15 - 20mm to fit with different T-grids
- Designed for various Rockfon tiles (E, X, M & D-edge)
- Specific corner caps available
- Used with hold-down clips to close gaps between grid and tiles
- Compatible with a variety of hold-down clips according to tile thickness
- Perfect colour match with ceiling grids

Assortment

Product group		Component description	Length (mm)	Colour	Pcs per pack	Lm per pack	Kg per pack
Wall angle options							
W20x10x10x14		W Profile 20 x 10 x 10 x 14mm	3000	02	40	120	20
W15x20x20x20		W Profile 15 x 20 x 20 x 20mm	3000	02	40	120	32.5
W22x15x15x15		W Profile 22 x 15 x 15 x 15mm	3000	02	40	120	28.5
Accessories							
CC W8x12 OUT		Outside stepped corner for W-profile 15x8x12x15 mm		001	50		1.1
CC 15 OUT		Outside flat corner for W-profile flange 15 mm		11, 001	50		0.85
CC W8x12 IN		Inside stepped corner for W-profile 15x8x12x15 mm		001	50		1.3


Product description

W20x10x10x14




- • Shadow angle with a 14mm face and a 20mm mounting surface.
 - Suitable for semi-concealed and concealed tiles of 10mm
 - Material thickness: 0.4mm
- Body Material thickness**0.4mm

W15x20x20x20



- • Shadow angle with a 20mm face and a 15mm mounting surface.
 - Suitable for semi-concealed and concealed tiles of 20mm
 - Material thickness: 0.4mm
- Body Material thickness**0.4mm

W22x15x15x15



- • Shadow angle with a 15mm face and a 22mm mounting surface.
 - Suitable for semi-concealed and concealed tiles of 15mm
 - Material thickness: 0.4mm
- Body Material thickness**0.4mm

Performance



Reaction to fire
Non-combustible



Environment
Fully Recyclable

Rockfon® is a registered trademark
of the ROCKWOOL Group.

 [linkedin.com/company/Rockfon-as](https://www.linkedin.com/company/Rockfon-as)

 [pinterest.com/Rockfon](https://www.pinterest.com/Rockfon)

 [youtube.com/RockfonOfficial](https://www.youtube.com/RockfonOfficial)

 [facebook.com/RockfonOfficial](https://www.facebook.com/RockfonOfficial)

 [instagram.com/Rockfon_Official](https://www.instagram.com/Rockfon_Official)

03.2022 | All colour codes mentioned are based on the NCS - Natural Colour System® property of and used on
license from NCS Colour AB, Stockholm 2012 or the RAL colour standard. Subject to alterations in range and product
technology without prior notice. Rockfon accepts no responsibility for printing errors.

Sounds Beautiful

Rockfon Singapore

ROCKWOOL Building Materials
(Singapore) Pte Ltd.
No. 7, Tuas Avenue 1
Jurong Town,
Singapore 639492
Tel: (+65) 6861 4722
Fax: (+65) 6862 3533
E-mail: enquiry@rockfon.com
en.rockfon.international

Rockfon Hong Kong

ROCKWOOL Building Materials
(Hong Kong) Ltd.
Unit 301-2, 3/F, Koon Wah Building,
No.2 Yuen Shun Circuit,
Yuen Chau Kok, Shatin,
N.T., Hong Kong
Tel: (+852) 2576-6117
Mobile: (+852) 9161-7924
E-mail: enquiry@rockfon.com
en.rockfon.international

Rockfon

ROCKWOOL Middle East FZE
Office 139, Building 6WB, DAFZA
P. O. Box 293585, Dubai, UAE

Tel: +971-4-214-6280
E-mail: rockfonme@rockfon.com
en.rockfon.international

Rockfon

ROCKWOOL France S.A.S.
111, rue du Château des Rentiers
75013 Paris

Tel: +33 1 40 77 82 82
Fax.: +33 1 45 86 77 90
E-mail: info@rockfon.fr
www.rockfon.fr

