


DATASHEET

Rockfon Color-all®



Rockfon Color-all®

- 34 exclusive colours for acoustic ceiling and wall solutions to inspire and enhance your interior design scheme
- Subtle yet playful colours made to mix and match either within the same room or in different areas of a building
- Total design freedom due to exposed, semi-concealed and concealed edges in a large variety of module sizes

Product Description

- Stone wool tile
- Visible side: smooth coloured, matt fleece
- Rear side: back fleece

Application Areas

- Industry
- OfficeLeisure
- Retail
- Education
- Healthcare

Edge detail	Module size (mm)	Approximate weight (kg/m²)	Recommended installation System	Recycled content	Cradle to Cradle Certified®	A1-A3 Production stage impact (kg CO ₂ eq/m²)*	A1-C4 Full life cycle impact (kg CO ₂ eq/m²)*
A15	600 x 600 x 15	2.2	Rockfon® System T15 A™	36%	CERTIFIED 8 cradle to cradle SILVER	1.96	2.53
	600 x 600 x 15	2.2	Rockfon® System T24 A™		CERTIFIED © cradle to cradle	1.96	2.53
A24			Chicago Metallic™ T24 1812	36%			
	600 x 600 x 20	3.4	Rockfon® System T24 E™				
E24			Chicago Metallic™ T24 1812	38%	CERTIFIED cradle silver	3.3	4.26
Х		3.7	Chicago Metallic™ T24 1812		CERTIFIED 8 cradle to cradle SILVER	3.48	4.53
	600 x 600 x 22		Chicago Metallic™ T24 3830	38%			


Rockfon Color-all Special is a bespoke colour matching service for both tiles and grids using NCS references. For specific pricing and minimum quantities, please call for details.

^{*} For full environmental impact disclosure, see our product EPDs available on rockfon.link/int-epd. Due to differences in calculation methods and scenario assumptions, environmental impact values are generally not directly comparable between manufacturers.



Performance





ı	A: 15 / 200	0.50	0.85	0.95	0.85	1.00	1.00	0.95	Α	0.90
ı	E: 20 / 200	0.45	0.85	0.95	0.90	1.00	1.00	0.95	Α	0.95
	X: 22 / 200	0.45	0.85	0.90	0.90	1.00	1.00	0.95	А	0.95



Reaction to fire

Color-all Mercury: Class A2-s1,d0



Light reflection

Colour-dependent



Humidity and sag resistance

Up to 100% RH. No visible deflection in high humidity.

C/0N



Cleaning

Vacuum



Hygiene

Stone wool provides no sustenance to microorganisms



Recyclability

Fully recyclable stone wool



Indoor environment

Rockfon ceiling products are classified in Class E1 in accordance with EN 13964 (EN 717-1). Rockfon ceiling products have a very low release of VOCs. A selection of Rockfon products have achieved the following performance levels and labels in indoor air emissions:








Material Health

All materials used in Rockfon products are screened against the technical checklist A20 and the list of substances restricted under REACH and do not contain substances of very high concern (SVHC). Rockfon stone wool fibres comply with safe fibre EU regulation and hold a EUCEB certification.

Rockfon Color-all®



NCS codes are closest colour match - contact us for more information. The actual colour of the ceiling tiles may deviate slightly from printed colours due to the texture of the surface and the underlying colour of stone wool. Samples of the coloured surfaces are available upon request.

Sounds Beautiful