

DATASHEET

# **Rockfon® Tropic**



# **Rockfon® Tropic**

- Smooth attractive white surface for various of applications
- Class A sound absorption
- Full range of formats in semi-concealed and visible grid options
- Easy to clean with a vacuum

## **Product Description**

- Stone wool tile
- Visible side: smooth white painted fleece
- Rear side: back fleece
- Painted edges

# **Application Areas**

- Office
- Education
- Leisure
- Retail

Edge detail	Module size (mm)	Approximate weight (kg/m²)	Recycled content	Cradle to Cradle Certified®	A1-A3 Production stage impact (kg CO <sub>2</sub> eq/m²)*	A1-C4 Full life cycle impact (kg CO₂ eq/m²)*	
A15	600 x 600 x 15 1200 x 600 x 15	2.0	33%	cradle to cradle	1.99	2.45	
	600 x 600 x 20	2.4	35%				
	1200 x 600 x 20				2.49	3.09	
	600 x 600 x 15	2.0	33%	CERTIFIED Cradle to cradle	1.99	2.45	
A24	1200 x 600 x 15				1.99	2.45	
	600 x 600 x 20	2.4	35%		2.49	3.09	
	1200 x 600 x 20						
	1800 x 600 x 20						
	600 x 600 x 15	2.2	35%	CERTIFIED STATES			
E15	1200 x 600 x 15				2.33	2.93	
	600 x 600 x 15	2.2	35%	CERTIFIED Cradle Cradle to Cradle	2.22	2.93	
E24	1200 x 600 x 15	2.2			2.33		
	600 x 600 x 20	2.8	36%		2.74		
	1200 x 600 x 20					3.52	

<sup>\*</sup> For full environmental impact disclosure, see our product EPDs available on rockfon.link/int-epd. Due to differences in calculation methods and scenario assumptions, environmental impact values are generally not directly comparable between manufacturers.



1.0

# **Performance**



Sound absorption  $\alpha_{\text{w}}\!\!:$  up to 1.00 (Class A)

0.9 8.0 0.7 0.6  $\alpha_p \ 0.5$ 0.4 0.3 0.2 0.1 0.0 Edge / Thickness (mm) / Suspension (incl. tile - mm) 125 Hz 250 Hz 500 Hz 1000 Hz 2000 Hz 4000 Hz

A,E: 15 / 200	0.40	0.75	0.95	0.90	1.00	1.00	0.95	А	0.90
A: 20 / 200	0.60	0.90	1.00	0.95	1.00	1.00	1.00	Α	1.00
A,E: 20 / 200	0.60	0.90	1.00	0.95	1.00	1.00	1.00	А	1.00



Reaction to fire Α1



**Light reflection** 86%



**Humidity and sag resistance** Up to 100% RH. No visible deflection in high humidity. C/0N



## Cleaning

Vacuum



Stone wool provides no sustenance to microorganisms



# Recyclability

Fully recyclable stone wool



## Indoor environment

Rockfon ceiling products are classified in Class  ${\sf E1}$  in accordance with EN 13964 (EN 717-1). Rockfon ceiling products have a very low release of VOCs. A selection of Rockfon products have achieved the following performance levels and labels in indoor air emissions:

Absorption class

NRC







### **Material Health**

All materials used in Rockfon products are screened against the technical checklist A20 and the list of substances restricted under REACH and do not contain substances of very high concern (SVHC). Rockfon stone wool fibres comply with safe fibre EU regulation and hold a EUCEB certification.

# **Sounds Beautiful**