

Rockfon® Curvgrid™ EZ-flex®

Features & Benefits

- Create dramatic arch ceilings, waves, vaults and islands for interior spaces
- Curved and straight main tees connect with straight cross tees to form 24" wide ceiling modules
- Concealed main tees, cross tees and obscured perimeter trim provide "frameless" appearance
- Primary Carrier support for tees and trim requires fewer hanger wires
- Use with or without flexible infill panels

Applications

- Auditoriums
- Lobbies
- Retail
- Schools
- Hospitality



Rockfon® Curvgrid™ EZ-flex®

Product Code Example: 252574:CRVG:CEFP:2448:AA:805:.32AL


LEED® V4 HIGHLIGHTS

Materials and Resources (MR)

Waste Management Planning Interiors Life Cycle Impact Reduction Environmental Product Declarations Sourcing of Raw Materials Material Ingredients Indoor Environmental Quality (EQ)
Low-Emitting Materials

Low-Emitting Materials
Interior Lighting
Acoustic Performance

Recycled Content: up to 85%



					7,4		<u></u>	
Family Number & Name	Detail	Dimensions	Perforations* (% open area)	Material	NRC	Fire Class	Light Reflectance	Low VOC
252574:CRVG: Curvgrid [™] Metal Panel	CEFP: EZ-flex®	2424: 24" x 24" Panel 2448: 24" x 48" Panel 2472: 24" x 72" Panel 2496: 24" x 96" Panel CUST: **	Standard SOLID: 0% V: 4.9% AA: 2.5% Premium see footnote * Custom CUST: **	.32AL: 0.032" Aluminum	up to 0.90***	А	-	~

^{*} For graphic representations of the perforation options, see the Rockfon Perforations Brochure.

Note:

- Curvgrid EZ-flex metal panels have integral tabs for attachment to Curvgrid Suspension Tee see Curvgrid EZ-flex details.
- See Curvgrid EZ-flex Suspension chart for minimum radius information.
- Acoutex™ Backer standard with perforated panel.
- Perforated panel available without Acoutex.

Choose from the above product options to build your product code

Family Number & Name	Detail	Standard Dimensions or Custom Dimensions	Perforation	Color*	Material
252574:CRVG:	CEFP:				.32AL

^{*} Select one of our many color options, located on page 3

^{**} For designer specified Dimensions or Perforation, contact Rockfon Technical Services at 1-800-323-7164 or techservices@rockfon.com.

^{***} NRC values are dependent on perforation patterns, plenum depth and acoustical backer options. Contact Rockfon Technical Services for more information at 1-800-323-7164 or techservices@rockfon.com.



^{*} Coordinating solid color to match Metalwood Woodgrain Finishes.

Note

Colors shown are reproduced as close as possible to actual product color within the limitations of printing technology. Color chips are available upon request and should be reviewed before making a final selection. Variations in color matches of system components to ceiling panels can result from slight differences in texture, room lighting, painting process and subjectivity of observers.

^{**} Metalwood Woodgrain Finishes not available for Rockfon Curvgrid Suspension, CurvTrim or panels wider than 24"; use coordinating solid color. See footnote *.

[▲] Metalwood Woodgrain Finishes are a 0.008" vinyl laminate that replicate real wood; variations in color and pattern will occur. For final panel thickness information contact Rockfon Technical Services at 1-800-323-7164 or techservices@rockfon.com. For interior use only.

[†] Woodscenes Painted Finishes are a decorative powder coat finish that replicate real wood; variations in color and pattern will occur.


⁻ Metalwood and Woodscenes grain direction is parallel to the length of the panel.

⁻ See rockfon.com for more information on color options.

Curvgrid EZ-flex Suspension

Detail	Product Number	Length	Slotting	Spacing	Finish			
Curvgrid Suspension Tee (Convex, Concave and Straight)*								
1-1/2"	Main Tee** (Main Runner) Cross Tee**	Main Tee 144" - Standard Cross Tee 24" - Standard	Main Tee 24" O.C Standard Cross Tee no slotting	Main Tee 24" O.C Standard (Custom Spacing available) Cross Tee as required	see footnote ***			
Primary Carrier								
1-1/2" —	249651 481.024.008	as required per design	-	48" O.C. Standard	08 Black			

CurvTrim Perimeter Trim



Note:

- 36" minimum convex and concave radius.
- Available in Standard, Premium, Metallic and Woodscenes finishes.

^{*} Minimum convex and concave suspension radius is 36".

** Curvgrid Suspension Tee made to order per design. For ordering information, contact Rockfon Technical Services at 1-800-323-7164 or techservices@rockfon.com.

^{***} Available in Standard, Premium, Metallic and Woodscenes finishes.

Curvgrid EZ-flex System Accessories



Splice Plate (Curvgrid Main Tee) (galvanized) 250327 436.00



Grid Attachment Clip (Curvgrid to CurvTrim) (galvanized) 249362 433.00



Clip (Primary Carrier to Curvgrid) (galvanized) 249365 442.00



Splice (Primary Carrier) (galvanized) 249367 444.00



Clip (Primary Carrier to Hanger Wire) (galvanized) 250328 441.00



Clip (Primary Carrier to CurvTrim) (galvanized) 249366 443.00



Splice Plate (CurvTrim) (galvanized) 249363 434.00



Splice Plate (CurvTrim Outside Corner) (galvanized) 249360 429.00



Acoustical Pads (Poly-Wrapped Fiberglass) (Black Plastic Wrap)

24" x 24" x 1" 250505 58.01.059.008

24" x 24" x 1-1/2" 250509

58.01.064.008


24" x 48" x 1" 250507 58.01.061.008

24" x 48" x 1-1/2" 250508


58.01.063.008

Curvgrid Standard Details


Curvgrid Tee to CurvTrim with Grid Attachment Clip



CurvTrim Splice Plate Connection




Curvgrid Tee Splice Plate Connection




Curvgrid EZ-flex Details


Panel at CurvTrim





Panel at Curvgrid Tee



Curvgrid Design Layout Examples










Curvgrid EZ-flex System Detail



Curvgrid EZ-flex System Detail Notes:

⁻ See rockfon.com for more product information.



Material

0.032" Aluminum



Fire Performance

Surface burning characteristics: UL723 (ASTM E84) Flame Spread Index: 0 Smoke Developed Index (UL Labeled): 0



Hygiene

Metal provides no sustenance to microorganisms



Warranty

1-Year Limited Product Warranty. See rockfon.com



Environment

- Up to 85% recycled content
- 100% locally recyclable



Cleaning

- Damp Cloth

080819

Rockfon

4849 S. Austin Ave. Chicago, IL 60638 USA

Tel. +1-800-323-7164 Fax. +1-800-222-3744 rockfon.com

2019 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

ROCKWOOL International A/S 2018. All rights reserved.

[®] denotes a trademark that is registered in the United States of America.