

Rockfon® Alaska®


UP TO
0.90
NRC

Features & Benefits

- Elegant smooth white surface
- High sound absorption (NRC = 0.70 - 0.90)
- Fire Performance - Class A
- High light reflectance (LR = 0.86)
- Optimal design freedom thanks to a large selection of edges (lay-in, tegular and concealed)

Applications

- Office
- Classroom
- Reception
- Multi-Purpose
- Auditorium



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



High Acoustic Absorption



Fire Performance - Class A



Moisture and Sag Resistance



Smooth, Modern Aesthetics

Materials and Resources (MR)

Waste Management Planning
 Interiors Life Cycle Impact Reduction
 Environmental Product Declarations
 Sourcing of Raw Materials
 Material Ingredients
 Waste Management

Indoor Environmental Quality (EQ)







Low-Emitting Materials ✓
 Interior Lighting ✓
 Acoustic Performance ✓

Recycled Content: 49%



Packaging Information

Standard Panels

Edge Designation		Item Number	Modular Size (nominal)*	NRC	AC	Fire Class	Light Reflectance	Sag Resistance (relative humidity)	Low VOC	lbs/sqft	sqft/carton
 Square Lay-In	SQ	10100	2' x 2' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	80
	SQ	10101	2' x 4' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	80
	SQ	10102	2' x 5' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	100
	SQ	10103	2' x 6' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	120
	SQ	10105	30" x 30" x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	37.5
 Square Tegular Narrow	SLN	10200	2' x 2' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	40
	SLN	10201	2' x 4' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	80
	SLN	10202	2' x 5' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	80
	SLN	10203	2' x 6' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	96
	SLN	10205	30" x 30" x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	37.5
 Angled Tegular	SLT	10300	2' x 2' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	40
	SLT	10301	2' x 4' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	80
	SLT	10302	2' x 5' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	80
	SLT	10303	2' x 6' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	96
 Direct Mount	DMT	10350	2' x 2' x 3/4"	0.70	180	A	0.86	up to 100%	✓	0.69	40
	DMT	10351	2' x 4' x 3/4"	0.70	180	A	0.86	up to 100%	✓	0.69	80
 Semi-Concealed	SCD	10550	2' x 2' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	40
	SCD	10551	2' x 4' x 3/4"	0.90	180	A	0.86	up to 100%	✓	0.69	80
 Fully Concealed	CDX	10600	2' x 2' x 7/8"	0.90	180	A	0.86	up to 100%	✓	0.75	40
	CDX	10601	2' x 4' x 7/8"	0.90	180	A	0.86	up to 100%	✓	0.75	80

*Refer to the Rockfon® Module System brochure for module tile sizes.

15/16" Suspension Systems				9/16" Suspension Systems				
200, 1200 and Fire Rated systems				4000, 4200, 4500, 4600 and Fire Rated systems				
SQ - Square Lay-In	SLT - Angled Tegular	SCD - Semi-Concealed	CDX - Fully Concealed	SQ - Square Lay-In (2' x 2' & 2' x 4' only) <div> SLN - Square Tegular Narrow </div>				
				4000 - Tempra	4000 - Tempra	4200 - Integrity	4500 - Ultraline 1/4" reveal	4600 - Ultraline 1/8" reveal

Recycled content values for our stone wool tiles and panels are based on 2021 production averages of a standard 2' X 2' tile, and based on their primary production location.



Rockfon® Alaska® Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint on glass scrim surface
ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



Fire Performance

Surface burning characteristics:
UL723 (ASTM E84) Flame Spread Index: 0
Smoke Developed Index (UL Labeled): 5
CAN/ULC S102 Flame Spread Index: 5
Smoke Developed Index: 0



Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen

- ✓ GREENGUARD Gold available*
- ✓ Environmental Product Declaration available*
- ✓ Health Product Declaration available*
- ✓ Declare Label available*

* Applicable to all edge types



Environment

49% recycled content. Recycled content based on U.S. manufacturing.



Warranty

30-Year Limited Product Warranty
See rockfon.com



Thermal Insulation

R Value (BTU Units): 2.6 - 3.1
RSI Value (Watts Units): 0.46 - 0.54



Hygiene

Stone wool provides no sustenance to microorganisms



Cleaning

Vacuum



GREENGUARD Gold Certified
for Office and Educational
Environments



CERTIFIED Environmental
Product Declaration

032023

Rockfon

4849 S. Austin Ave.
Chicago, IL 60638 USA

2023 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.
© ROCKWOOL A/S 2023. All rights reserved.

® denotes a trademark that is registered in the United States of America.

Tel. +1-800-323-7164
cs@rockfon.com
rockfon.com