

# Rockfon® Color-all™

UP TO  
**0.95**  
NRC

## Features & Benefits

- 34 exclusive colors for acoustic ceiling and wall solutions to inspire and enhance your interior design scheme
- Smooth surface
- Excellent sound absorption (NRC = 0.85 - 0.95)
- Fire Performance - Class A
- Optimal design freedom due to the variety of edges (lay-in, tegular and concealed) and colors

## Applications

- Office
- Industry
- Healthcare
- Retail
- Classroom
- Restaurant
- Reception
- Auditorium



**mindful**  
MATERIALS



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



**High Acoustic  
Absorption**



**Fire Performance -  
Class A**



**Moisture and  
Sag Resistance**



**Smooth, Modern  
Aesthetics**

### Materials and Resources (MR)

Waste Management Planning  
 Interiors Life Cycle Impact Reduction  
 Environmental Product Declarations  
 Sourcing of Raw Materials  
 Material Ingredients  
 Waste Management

### Indoor Environmental Quality (EQ)

Low-Emitting Materials ✓  
 Interior Lighting ✓  
 Acoustic Performance ✓

Recycled Content 41%



## Standard Panels



### Packaging Information

Edge Designation		Item Number	Modular Size (nominal)*	NRC	Fire Class	Light Reflectance	Sag Resistance (relative humidity)	Low VOC	lbs/sqft	sqft/carton
	SQ	11100	2' x 2' x 5/8"	0.90	A	Color Dependant	up to 100%	✓	0.47	112
	SQ	11101	2' x 4' x 5/8"	0.90	A	Color Dependant	up to 100%	✓	0.47	112
	SL	11250	2' x 2' x 3/4"	0.95	A	Color Dependant	up to 100%	✓	0.69	40
	SL	11251	2' x 4' x 3/4"	0.95	A	Color Dependant	up to 100%	✓	0.69	80
	SLN	11200	2' x 2' x 3/4"	0.95	A	Color Dependant	up to 100%	✓	0.69	40
	SLN	11201	2' x 4' x 3/4"	0.95	A	Color Dependant	up to 100%	✓	0.69	80
	CDX	11600	2' x 2' x 7/8"	0.95	A	Color Dependant	up to 100%	✓	0.75	40
	CDX	11601	2' x 4' x 7/8"	0.95	A	Color Dependant	up to 100%	✓	0.75	80

Recycled content values for our stone wool tiles and panels are based on 2020 production averages of a standard 2' X 2' tile and based on their primary production location.

\* Refer to the Rockfon® Module System brochure for module tile sizes.

### Minimum Order Quantities for Rockfon® Color-All™

All Rockfon Color-All Square Edge (SQ) 2'x2' and 2'x4' tiles = 300 sqft minimum. Minimums do not apply to Color-all Standard Program. \*\* For any other sizes, please contact Rockfon Customer Service.





SL, SLN, and CDX edges in all dimensions in all 34 Color-all colors = 6,000 sqft. Minimums do not apply to Color-all Standard Program. \*\*

(Different edges and dimensions can be mixed in the same color. The quantity per dimension/edge must be 1,000 sqft and the total quantity must be 6,000 sqft.)

\*\* Minimum order quantities do not apply to matching Color-All grid products and 4 Color-all Standard Program Colors: 701 Stone, 706 Concrete, 723 Hemp, 709 Charcoal. For further questions please contact Rockfon Customer Service.

15/16" Suspension Systems	9/16" Suspension Systems
200, 1200 and Fire Rated systems	4000, 4200, 4500 and Fire Rated systems
SQ - Square Lay-In    SL - Square Tegular    CDX - Fully Concealed 	SLN - Square Tegular Narrow 

# Rockfon® Color-all™ Standard Program Colors

 Charcoal Light reflectance: 0.04	 Concrete Light reflectance: 0.16	 Hemp Light reflectance: 0.45	 Stone Light reflectance: 0.55
--	--	--	--
















Please refer to Rockfon® Color-all™ Standard Program Datasheet for more details.

## Additional Rockfon® Color-all™ Colors

 Mustard Light reflectance: 0.36	 Sand Light reflectance: 0.55	 Stucco Light reflectance: 0.70	
 Scarlet Light reflectance: 0.08	 Coral Light reflectance: 0.21	 Seashell Light reflectance: 0.55	 Petal Light reflectance: 0.70
 Seaweed Light reflectance: 0.05	 Eucalyptus Light reflectance: 0.12	 Sage Light reflectance: 0.34	 Mint Light reflectance: 0.70
 Space Light reflectance: 0.04	 Storm Light reflectance: 0.08	 Azure Light reflectance: 0.34	 Fresh Light reflectance: 0.51

The actual color of the ceiling tiles may deviate slightly from printed colors due to the texture of the surface and the underlying color of stone wool. Samples of the colored surfaces are available upon request.

# Additional Rockfon® Color-all™ Colors

 <div>Earth</div> <div>725</div>	 <div>Clay</div> <div>726</div>	 <div>Linen</div> <div>722</div>	 <div>Sandalwood</div> <div>713</div>	 <div>Chalk</div> <div>721</div>
Light reflectance: 0.22	Light reflectance: 0.22	Light reflectance: 0.29	Light reflectance: 0.49	Light reflectance: 0.51
 <div>Ebony</div> <div>728</div>	 <div>Cork</div> <div>724</div>			
Light reflectance: 0.04	Light reflectance: 0.30			
 <div>Iron</div> <div>718</div>	 <div>Mastic</div> <div>704</div>	 <div>Zinc</div> <div>705</div>	 <div>Mercury</div> <div>762</div>	
Light reflectance: 0.07	Light reflectance: 0.33	Light reflectance: 0.33	Light reflectance: 0.44	
 <div>Anthracite</div> <div>708</div>	 <div>Gravel</div> <div>703</div>	 <div>Plaster</div> <div>702</div>	 <div>Moon</div> <div>710</div>	
Light reflectance: 0.07	Light reflectance: 0.34	Light reflectance: 0.58	Light reflectance: 0.74	

*The actual color of the ceiling tiles may deviate slightly from printed colors due to the texture of the surface and the underlying color of stone wool. Samples of the colored surfaces are available upon request.*





## Rockfon® Color-all™ Properties

### Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint on glass scrim surface  
 ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



#### Fire Performance

Surface burning characteristics:  
 UL723 (ASTM E84) Flame Spread Index: 5-15  
 Smoke Developed Index (UL Labeled): 0  
*Flame Spread Index is color dependant*



#### Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen

- ✓ GREENGUARD Gold available\*
- ✓ Environmental Product Declaration available\*

\* Applicable to all edge types



#### Cleaning

Vacuum



#### Environment

41% recycled content. Recycled content based on European manufacturing.



#### Warranty

30-Year Limited Product Warranty  
 See [rockfon.com](http://rockfon.com)



#### Thermal Insulation

R Value (BTU Units): 2.2 - 3.1  
 RSI Value (Watts Units): 0.39 - 0.54



#### Hygiene

Stone wool provides no sustenance to microorganisms



GREENGUARD Gold Certified  
 for Office and Educational  
 Environments



CERTIFIED Environmental  
 Product Declaration

031323

**Rockfon**

4849 S. Austin Ave.  
 Chicago, IL 60638 USA

2023 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.  
 © ROCKWOOL A/S 2023. All rights reserved.

® denotes a trademark that is registered in the United States of America.

Tel. +1-800-323-7164  
[cs@rockfon.com](mailto:cs@rockfon.com)  
[rockfon.com](http://rockfon.com)