

Rockfon® Color-all™ Standard Program

UP TO
0.95
NRC

Features & Benefits

- Charcoal, Concrete, Stone and Hemp available at faster service level for the standard tile & grid sizes in smaller quantities
- Optimal design freedom due to the variety of colors and edges types (SQ, SL, SLN, CDX)
- Color-all grid now has a smooth matte finish
- Excellent sound absorption (NRC= 0.85- 0.95)
- Fire Performance - Class A
- Module sizes available. Please refer to the Rockfon® Module System Brochure for module tile sizes.

Applications

- Office
- Industry
- Healthcare
- Retail
- Classroom
- Restaurant
- Reception
- Auditorium



mindful
MATERIALS



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



High Acoustic Absorption



Fire Performance - Class A



Moisture and Sag Resistance







Smooth, Modern Aesthetics

Rockfon® Color-all™ Standard Program

Square Lay-in (SQ), Square Tegular (SL), Square Tegular Narrow (SLN), and Fully Concealed (CDX) panels and below suspension systems are available in the following Color-All™ colors:

Updated Tile and Grid Color Offerings

All Smooth Matte Finish





	Color Name
	701 Stone
	706 Concrete
	723 Hemp
	709 Charcoal

Grid Selection with Updated Color Offering

Part Description	Part Number			
	Suspension System		Feet/Carton	
	1200 15/16"	4000 9/16"		
Main Runner	211.XXX (ID) 200.XXZ.XXX (HD)	4000.XXX	240	
2" Cross Tee	1202.XXX	4022.XXX	120	
Wall Angle	1420.XXX	1480.XXX	504	300

Last digits in part numbers correspond to tile color number.

Tile Selection with Updated Color Offering

Edge Designation	Part Number	Modular Size	Square Feet/Carton
Square Lay-in 	11100	2' x 2' x 5/8"	112
Square Tegular 	11250	2' x 2' x 3/4"	40
Square Tegular Narrow 	11200	2' x 2' x 3/4"	40
Fully Concealed 	11600	2' x 2' x 7/8"	40

Refer to the Rockfon® Module System brochure for module tile sizes.





Rockfon® Color-all™ Standard Program Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint on glass scrim surface
ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



Fire Performance

Surface burning characteristics:
UL723 (ASTM E84) Flame Spread Index: 5-15
Smoke Developed Index (UL Labeled): 0
Flame Spread Index is color dependant



Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen

- ✓ GREENGUARD Gold available*
- ✓ Environmental Product Declaration available*

* Applicable to all edge types



Cleaning

Vacuum



Environment

41% recycled content. Recycled content based on European manufacturing.



Warranty

30-Year Limited Product Warranty
See rockfon.com



Thermal Insulation

R Value (BTU Units): 2.2 - 3.1
RSI Value (Watts Units): 0.39 - 0.54



Hygiene

Stone wool provides no sustenance to microorganisms



Tile Directionality

Rockfon® Color-all™ - DC tiles are directional and must be installed according to backside arrow direction. The arrow can be turned 180°, not 90°



GREENGUARD Gold Certified
for Office and Educational
Environments



CERTIFIED Environmental
Product Declaration

061223

Rockfon

4849 S. Austin Ave.
Chicago, IL 60638 USA

2023 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.
© ROCKWOOL 2022. All rights reserved.

® denotes a trademark that is registered in the United States of America.

Tel. +1-800-323-7164
cs@rockfon.com
rockfon.com