

Rockfon® Contour™

Features & Benefits

- Innovative and aesthetically-pleasing frameless acoustical baffle
- High sound absorption contributes to acoustic comfort
- Fast and easy to install
- Ideally-suited for acoustical corrections
- Fire Performance - Class A

Applications

- Office
- Retail
- Restaurant
- Open Plan Space



mindful
MATERIALS



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



**High Acoustic
Absorption**



**Fire Performance -
Class A**



**Moisture and
Sag Resistance**



**Smooth, Modern
Aesthetics**

Materials and Resources (MR)






- Waste Management Planning
- Interiors Life Cycle Impact Reduction
- Environmental Product Declarations
- Sourcing of Raw Materials
- Material Ingredients
- Waste Management

Indoor Environmental Quality (EQ)

- Low-Emitting Materials
- Interior Lighting
- Acoustic Performance

Recycled Content: up to 42%

Standard Panels

								Packaging Information	
Edge Designation		Item Number	Modular Size (nominal)	Fire Class	Light Reflectance	Sag Resistance* (relative humidity)	Low VOC	lbs/unit	units/carton
Square Chamfered 	SQc	7200	12" x 48" x 2"	A	0.79	up to 100%	✓	5.07	12
	SQc	7225	24" x 48" x 2"	A	0.79	up to 100%	✓	10.14	6

*Rockfon Contour is not suitable for use in swimming pools or outdoors.



Rockfon® Contour™ Properties

Material

Stone wool (Mineral Wool) frameless baffle with factory applied latex paint on glass scrim surface on both sides of baffle
ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



Fire Performance

Surface burning characteristics:
UL723 (ASTM E84) Flame Spread Index: 0
Smoke Developed Index (UL Labeled): 5
CAN/ULC S102 Flame Spread Index: 5
Smoke Developed Index: 0



Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen



Environment

Up to 42% recycled content. Recycled content based on U.S. manufacturing.



Warranty

30-Year Limited Product Warranty
See rockfon.com



Hygiene

Stone wool provides no sustenance to microorganisms



Cleaning

Vacuum



Acoustical Properties

		Sabins per baffle					
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
Tested in ISO Type J mounting: 3 x 15'9" rows, 2'9" row spacing	24" x 48" x 2"	3.5	4.0	7.1	8.5	8.4	7.8



GREENGUARD Gold Certified
for Office and Educational
Environments



CERTIFIED Environmental
Product Declaration

062521

Rockfon

4849 S. Austin Ave.
Chicago, IL 60638 USA

2021 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.
© ROCKWOOL International A/S 2018. All rights reserved.
® denotes a trademark that is registered in the United States of America.

Tel. +1-800-323-7164
Fax. +1-800-222-3744
rockfon.com