

## Rockfon® Education Plus Rockfon

Final Assembly: Marshall County, Mississippi, USA

**Life Expectancy:** 50 Year(s)

**Embodied Carbon:** 2.962 kg CO2-Eq **Declared Unit:** 1 m2 of installed ceiling tile

End of Life Options: Recyclable (89%), Landfill (11%)

## **Ingredients:**

Stone wool, biosoluble; Aluminum hydroxide; Fiberglass; Syrups, hydrolyzed starch; Phenol, polymer with formaldehyde<sup>1</sup>; Limestone; Water; Polyvinyl alcohol; Urea; Caprolactam; Laurolactam; Dodecanedioic acid, polymer with decanedioic acid, hexahydro-2H-azepin-2-one, 1,6-hexanediamine and hexanedioic acid; Hexamethylenediamine; Hexanedioic acid; Urea, polymer with formaldehyde<sup>1</sup>; Undisclosed (< 0.5%)<sup>2</sup>; 2-Propenoic acid, 2-methyl-, C12-15-branched and linear alkyl esters, polymers with cetyl methacrylate, Me methacrylate, polyethylene glycol methacrylate branched tridecyl ether and stearyl methacrylate; Residual oils (petroleum), solvent-dewaxed; Titanium dioxide; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate

<sup>1</sup>LBC Temp Exception RL-009 - Formaldehyde <sup>2</sup>LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

## Living Building Challenge Criteria: Compliant

## I-13 Red List:

□ LBC Red List Free % [
■ LBC Red List Approved VC

% Disclosed: 99.5% at 100ppm VOC Content: Not Applicable

□ Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

RXL-0015 EXP. 01 DEC 2024 Original Issue Date: 2021